


GDF ~ Silencieux flexible



Fiche technique

L'isolation du silencieux flexible GDF est 25mm. D'autres épaisseurs sont disponibles sur demande.

GDF

Centrum frequentie (Hz)

Ø (mm)	D (mm)	L	Gewicht (kg)	125	250	500	1000	2000	4000	8000	Verpakking
80	125	1000	0.8	5	9	19	34	50	48	37	45
100	150	1000	1.0	3	8	18	33	50	39	31	35
125	180	1000	1.2	3	7	17	33	50	35	27	24
140	180	1000	1.3	2	6	15	32	50	34	25	20
150	200	1000	1.4	2	6	15	32	49	33	24	20
160	200	1000	1.4	2	6	13	29	40	25	18	20
180	224	1000	1.6	1	5	12	29	38	21	14	15
200	250	1000	1.8	2	5	11	25	26	14	11	12
224	280	1000	2.0	1	4	11	24	25	13	10	9
250	300	1000	2.2	1	4	11	22	23	13	10	8
280	355	1000	2.5	1	4	11	24	21	11	9	6

GDF

300	355	1000	2.6	1	4	10	24	20	10	8	6
315	355	1000	2.8	1	4	9	18	20	10	8	6
355	400	1000	3.2	1	4	8	17	16	9	7	5
400	450	1000	3.6	1	4	8	10	12	8	7	3
450	500	1000	4.1	--	2	6	8	10	6	5	